


# **Square Series**


# **GWST 211PPB40**

**Square Series** 

Disc Harrow









## **Technical Specification**

| d    | Bore diameter  | 1.791 ind | ch |
|------|--|-----------|----|
| d    | Bore diameter  | 45.5 mi   | m  |
| В    | Width inner ring   | 45 mi     | m  |
| С    | Width outer ring   | 25 mi     | m  |
| a    | Shaft size   | 1.594 ind | ch |
| a    | Shaft size   | 40.5 mi   | m  |
| Da   | Centering diameter   | 113 mi    | m  |
| L    | Overall length   | 140 mi    | m  |
| Α    | Distance from the housing flange to the front of the inner ring of the bearing | 44.7 mi   | m  |
| A1   | Width of the top of the housing  | 4 mi      | m  |
| J    | Pitch circle diameter  | 140 mi    | m  |
| N    | Diameter of attachment slot  | 13.5 mi   | m  |
| Fr   | Radial load  | 9.8 kN    | ٧  |
| Fa   | Axial load   | 5.1 kN    | ٧  |
| kg   | Mass   | 2.25 kg   | 3  |
| Cdyn | Dynamic load rating  | 43.5 kN   | ١  |
| Со   | Static load rating   | 29 kN     | ٧  |
| Pu   | Fatigue load limit   | 1.218 kN  | ١  |



### Sealing

#### RUBBER PLUG + T SEAL / T SEAL + RUBBER PLUG

3-lip seal seal on both sides provide long lasting protection of the bearing against the penetration of contaminants. Rubber plugs are protecting the area between the bearing and sheet metal housing.

