


Housing units LEGS, four-bolt flanged housing units, cast iron, centring spigot, grub screw in inner ring, F seals

LEGS 216 2F.C82.6

Housing units LEGS, four-bolt flanged housing units, cast iron, centring spigot, grub screw in inner ring, F seals

Harvester Solution



Technical Specification

d	Bore diameter	80 mm
Da	Centering diameter	160 mm
L	Diameter of housings	220 mm
A	Distance from the housing flange to the front of the inner ring of the bearing	51.3 mm
A1	Housing flange thickness	18 mm
A2	Height of the housing	31 mm
J	Pitch circle diameter	184 mm
N	Hole diameter	18 mm
B	Width inner ring	82.6 mm
kg	Mass	5.308 kg
Cdyn	Dynamic load rating	72 kN
Co	Static load rating	54 kN
Pu	Fatigue load limit	2.268 kN

Sealing

F SEAL / F SEAL (2F)

Dual sealing, protection cover placed on the inner ring protects against rough impurity particles and makes the labyrinth with the sheet part of the seal; then the sealing S type,

with the labyrinth between the sheet part and the rubber lip that conducts the contact sealing. The friction and speeds are the same as with S but has much better protection

against rough impurity particles. It is very good sealing system: the sheet part protects the seal from the soil, dust and

rough particles. At the same time makes the labyrinth with the rubber part. The rubber part provides the contact sealing that prevents the penetration of the finer impurities, water, moisture, steam etc. Suitable for heavier conditions due to better protection against foreign matters. It is used with the Y bearings (standard).

